



Do More with A4

The TASKalfa 308ci is a powerful A4 color MFP for small to medium sized workgroups in medium to large corporate environment where durable operations and flexible finishing are required. It offers all the functionalities you would expect from a sophisticated MFP - easily accessible touchscreen, various paper handling options including 2,000-sheet large capacity paper feeder and 300-sheet internal finisher with 50-sheet stapling in 3 positions.



Specifications

GENERAL

KYOCERA TASKalfa Laser Color Multifunctional.

HvPAS™ Solution Platform

Operation panel: 177.8 mm (7 inch) full-color touch panel display, speaker for job notification, 0° - 90° swivel mounted **Engine speed** (pages per minute): Up to 30 pages A4 per minute Duplex print

speed: up to 30 page per minute A4 Duplex copy speed: 30 page per minute, A4 **Resolution:** 1200 x 1200 dpi, multibit technology for print quality of up to 9,600 equivalent x 600

dpi (print), 600×600 dpi (scan/copy) **Warm-up time:** Approx. 20 seconds or less from power on. **Time** to first print: Approx. 7.0 / 8.0 seconds or less in b/w/color Time to first copy: Approx. 6.4/ 7.8 seconds

or less in b/w/color (Platen)

CPU: Monaco (ARMCortex-A9 Dual core 1.2GHz+ARM Cortex-M3 100MHz)

Memory: Max. 3GB + 32GB or 128GB SSD Option

Standard interfaces: Standard interface: 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional USB 2.0 (High-Speed), Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots for optional internal print server, SSD hard disc or fax system, slot for optional SD Card.

Integrated accounting: 100 department codes Dimensions (W x D x H): 550 mm × 507.5 mm × 736.6 mm.

Weight: Main unit approx. 49.6 kg. Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption Print - mode: 510 Wh

Copy - mode: 510 Wh Low power mode: 38 Wh Ready mode: 69 Wh

Sleep mode: 0.5 Wh

Noise (Sound pressure level ISO 7779/ISO 9296)
Operation Mode: 65.4 dB(A)

Stand-by: 45dB(A)

Safety standards: TÜV/GS, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Standard universal paper cassette: 500 sheet 100-sheet multi-purpose tray,

 $60-220~{\rm g/m^2},~{\rm A4,~A5,~A6,~B5,~B6,~Letter,~Legal,}$ Folio, Custom (70 x 148 - 216 x 356 mm). Max.

input capacity with options: 3,100 sheets A4 **Duplex as standard unit**: 60–220 g/m², A4, A5, B5, Letter, Legal

Dual scan document processor as standard: 75 sheets, 50 - 120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm) Output capacity: 500-sheet-face-down

with paper full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE II c Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print. Operating systems: All current Windows operating systems, MAC OS X Version 10.8 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL6), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 (Bitmap font), 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417). Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,

SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality. Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Google cloud print.

COPY FUNCTIONS

Max. original size: A4/Legal Continuous copying: 1—999 Zoom range: 25—400% in 1% steps

Preset magnification ratios: 7 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 9 steps Image adjustments: Text + Photo, Photo,

Text, Map, Printed document

Features: Scan-once-copy-many, electronic sort (collate), ID card copy, 2in1, 4in1, auto cassette change, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN , WIA , WSD scan Scan speed: 40 ipm (300 dpi, A4, b/w), 30 ipm (300 dpi, A4 color), 17 ipm (300 dpi, A4, b/w)

(Duplex), 13 ipm (300 dpi, A4 color) (Duplex)

Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per color

Max. scan size: A4, Legal
Original recognition: Text, photo, text + photo, light text, Searchable PDF with OCR Option
File types: TIFF, PDF, PDF/A, JPEG, XPS, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b
Compression method: MMR /JPEG

Features: Color scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: Super G3 Modem speed: Max. 33.6 kbps Transmission time: Max. 3 seconds (JBIG) Scanning speed: 2.5 seconds/sheet

Address book: 200 entries Scanning density: Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi), Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi), Superfine 8 dot/mm x 15.4 line/mm (200 x 400 dpi), Ultrafine: 16 dot/ mm x 15.4 line/mm (400 x 400 dpi), Halftone: 256 grey scales Maximum original size: A4/Legal

Compression method: JBIG, MMR, MR, MH Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4 TK-5195K Toner Kit: Micro fine toner black for 15,000 pages A4 TK-5195C, TK-5195M, TK-5195Y: Micro fine toner cyan, magenta, yellow for 7,000 pages A4

Waste Toner Bottle: WT-5190 Waster Toner Bottle: 44,000 sheets . ______ with 5% coverage; b/w.color = 7:3) **Staple:** SH-10 Staple cartridge: 3 x 5,000 staples for DF-5100

OPTIONS

Fax System 11: Super G3 Fax, network fax Paper Handling: PF-5120: PF-5120 Paper feeder: 500 sheets,

60—220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 x 148 — 216 x 356 mm).

PF-5130*: Paper feeder : 2 x 500 sheets, $60-220 \text{ g/m}^2$, A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 x 148 - 216 x 356 mm). **PF-5140*:** Paper feeder : 2,000 sheets, 60–220 g/m², A4

DT-5100 Document tray: To place originals or USB Keyboard

JS -5100 Job separator: 100-sheet internal job separator, 60–220 g/m², A6 - A4/ Legal MT-5100**: 5-bin Mailbox sorter (**AK-5100), 5 bins x 100 sheets A4, 60–163 g/m², Main tray 500 sheets A4, 60-220 g/m². **DF-5100 Internal Document Finisher:** 300 sheets,

60—220 g/m², Stapling up to 50 sheets A4 at 3 positions. * Requires PF-5120

** Bridge unit AK-5100 is required for the use of MT-5100 HD-6 SSD: 32 GB for easy document management

HD-7 SSD: 128 GB for easy document management

SECURITY

Data Security Kit (E) for standard HD-6/HD-7 Memory Upgrade: MD3-1024, DDR3, 1GB UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): upport for various authentication keys available

IC Card Reader Holder 11: To integrate the USB IC Card Optional interface:

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT. IB-51: Wireless Lan (802.11b/g/n). IB-35: Wireless Network Interface

Cabinet:

CB-5110H: Wooden desk with storage capacity x. 550 mm x 510 mm x 500 mm (WxDxH). CB-5110L: Wooden desk with storage capacity Approx. 550 mm x 510 mm x 340 mm (WxDxH). CB-5120H: Metal desk with storage capacity. Approx. 550 mm x 510 mm x 500 mm (WxDxH). CB-5120L: Metal desk with storage capacity Approx. 550 mm x 510 mm x 340 mm (WxDxH)

The TASKalfa 308ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments















