



**Fact Sheet**

# PostBase™ Vision S3

**Features**

- Easy to use large, 5" color touchscreen
- Motorized, tilting display for best viewing angle
- Fast semi-automatic envelope processing at up to 35 letters/minute
- 5 lb. capacity integrated postal scale
- Differential weighing for integrated scale
- Rate wizard for USPS® postal products
- Automatic USPS® postal rate updates
- Integrated postage tape dispenser for parcels
- Supports USPS® DIM rating
- Secure PIN protection
- 6 customizable rate shortcuts
- 6 standard printable envelope graphics/adverts
- Up to 30 custom printable envelope graphics
- Create up to 12 different printable text messages or QR codes to promote your mail
- Received stamp for incoming mail
- Easiest ink replacement with on-screen guidance
- Connected to discover**FP** for easy mailing system management

**Options & Upgrades**

- Envelope moistener/sealer
- Integrated scale capacity upgrade to 10 or 15 lbs.
- Large platform external scale up to 70 lbs.
- Vision360 online postal analytics and reporting for up to 250 cost accounts
- FP Parcel Shipping
- Choose from 5 designer colors (Satin Steel/Black std.)



Satin Steel - Cashmere Blue - Marble White - Sahara Gold - NBCF® Pink

**Specifications**

- Dimensions: 17.9"(L) x 15.4"(D) x 11.3-12.9"(H)
- Expandable Catch Tray Length: 12.6"-17.5"
- System Weight: 22 lbs.
- Catch Tray Weight: 2.2 lbs.
- Envelope Sizes: 3.5" x 5" - 10" x 14"
- Maximum Envelope Thickness: .40"
- Noise Emission: <60 dB(A)

**Connectivity**

- High-Speed LAN or Built-in Wi-Fi

**Supplies**

- USPS® Certified **FP** Postal Inkjet Cartridge
- Postage Meter Strip Tapes
- SEALIT Envelope Sealing Fluid

**Postal Security Device (PSD/Meter)**

- USPS® IMI Approved (Highest Level)
- FIPS 140-2 Level 3 Cryptography Certified

**Manufacturing & Certifications**

- Manufactured: Wittenberge, Germany
- ISO-9001, 14001, 45001, 50001, 27001
- CE, GS, CSA, Nemko, UL Listed
- Complies with FCC Part 15, Subpart B, Class B

**Energy Consumption & Conservation**

- Operating Energy Consumption: 80W
- Standby Energy Consumption: 7W
- Switched Off Energy: 0.5W
- Electrical Requirements: 100-240V/2.0A/50-60Hz
- Energy Star® 2.0 Certified

