



**bizhub 950**i Black & White A3 multifunctional




Giving Shape to Ideas

### **CUSTOMER BENEFITS**



Intuitive operability Operate the bizhub like a smartphone or tablet with fully customized user interface

# **OPTIONS**





Security Secure network integration, data encryption and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio

.....

5



Productivity Reliability, high-speed scanning and printing, combined with powerful finishing functions

2




Services Efficient printer fleet management, including automatic consumables delivery, proactive maintenance and remote setup


Sustainability Numerous eco features reduce energy consumption and costs

2	CONNECTIVITY	
	Fax board FK-516 (Lines 1 & 2)	D
	Fax board FK-515 (Lines 3 & 4)	
	Wireless LAN UK-221	
	USBI/Fkit EK-610	2
	USB I/F kit EK-611	9
	Biometric authentication AU-102	2
	Card authentication AU-205H	צ
	Card authentication AU-205H	
	<b>Mount kit</b> MK-735	

3 OTHERS Working table WT-506 Upright panel WT-519 10-Key pad KP-102 Security kit SC-509 11B SSD EM-908 Keyboard holder KH-102 External Keyboard

OR





(4)

Staple finisher FS-540 Relay unit RU-515 Booklet finisher FS-540SD Relay unit RU-515 Punch kit for FS-540/SD PK-526 Post inserter for FS-540/SD PI-507 Job separator for FS-540/SD PS-602 Z-fold unit for FS-540/SD ZU-609



### **FINISHING FUNCTIONALITIES**



## DESCRIPTION

#### ENHANCED FEATURES

LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint <sup>®</sup> client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender <sup>®</sup> antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

#### CONNECTIVITY

FK-516 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authentication	Finger vein scanner
AU-204H Magnetic Stripe Card Reader	ID Card Authentication
AU-205H ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

OTHERS	
WT-506 Working table	Authentication device placement
WT-519 Upright panel	Working table for upright panel
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

External Keyboard

### MEDIA INPUT

LU-303 Large capacity tray	3,000 sheets, 8.5" x 11", 52-256 g/m <sup>2</sup>
LU-205 Large capacity tray	2,500 sheets, 8.5" x 11" - 12" x 18", 52-256 g/m <sup>2</sup>
MK-730 Banner tray	Multipage banner feeding

#### MEDIA OUTPUT

OT-508 Output tray	Output tray used instead of finisher
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3 hole punching; autoswitching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher;
	2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3 hole punching; autoswitching
RU-515 Relay unit	For FS-539/SD or FS-540/SD installation
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
ZU-609 Z-fold unit for FS-540/SD	Z-fold for 11" x 17" prints

# **TECHNICAL SPECIFICATIONS**

System speed Letter	Up to 95 ppm
System speed 11" x 17"	Up to 48 ppm
Auto duplex speed Letter	Up to 95 ppm
1st page out time Letter	3.2 sec.
Warm-up time	Less than 55 sec.
Imaging technology	Laser
Toner technology	Simitri <sup>®</sup> V polymerized toner
Panel size/resolution	10.1″ / 1024 x 600
System memory	8 GB (standard/max)
Solid State Drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 300 originals; 5.5" x 8.5" - 11" x 17"; 35-210 g/m <sup>2</sup> ;
	Dual scan ADF
ADF double feed detection	Standard
Printable paper size	4.5" x 5.5" - 12" x 18"; custom paper sizes;
	banner paper max. 47.2" x 11.7"
Printable paper weight	52-300 g/m <sup>2</sup>
Paper input capacity	3,650 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; 4.5" x 5.5"; custom sizes; 52-256 g/m <sup>2</sup>
	1x 500; 5.5" x 8.5"; 8.5" - 12" x 18"; custom sizes; 52-256 g/m <sup>2</sup>
	1x 1,500; 5.5" x 8.5"; 8.5" - 11" x 17"; 52-256 g/m²
	1x 1,000; 5.5" x 8.5"; 8.5" - 11" x 17"; 52-256 g/m²
Large capacity tray (optional)	1x 3,000; 8.5" x 11"; 52-256 g/m <sup>2</sup>
	1x 2,500; 8.5" x 11" - 12" x 18"; custom sizes; 52-256 g/m <sup>2</sup>
Manual bypass	150 sheets; 4.5" x 5.5" - 8.5" - 12" x 18"; custom sizes,banner;
	60-300 g/m <sup>2</sup>

#### SYSTEM SPECIFICATIONS

Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.5" x 5.5" - 12" x 18"; 52-256 g/m <sup>2</sup>
Output capacity	Up to 200 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m <sup>2</sup> )
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to $300 \text{ g/m}^2$ )
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Power consumption	208 V / 60 Hz, 20A; less than 3.8 kW
System dimension (W x D x H)	26.4" x 32.3" x 48.3" incl. ADF
System weight	Approx. 445 lbs (incl. ADF )

PRINT	rfr spr	ECIFICAT	IONS
			10113

Print resolution	600 x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5e/c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Windows Server 2022
	Macintosh OS X 10.13 or later;
	Mac OS 11/12 (AppleM1 chip-based PPD); Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android)
	optional: WiFi Direct

#### SCANNER SPECIFICATIONS

Scan speed	Up to 140/140 ipm in simplex (mono/color)
	Up to 280/280 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS
	PPTX; PDF/A 1a and 1b
	optional: Searchable PDF; Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

#### COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. 11" x 17"
Magnification	25-400% in 0.1% steps; Auto-zooming

#### FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

#### USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)







Works with

Apple AirPrint





Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO15408 Common Criteria; IP filtering and port blocking;
	SSL3 and TLS1.0/1.1/1.2/1.3 network communication;
	IPsec support;
	IEEE 802.1x support; User authentication; Authentication log;
	Secure print; Kerberos;
	Data encryption (AES 256); Confidential fax;
	Print user data encryption
	optional: Antivirus real-time scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Web Connection;
	Driver Packaging Utility; Log Management Utility

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

- <sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed
- All specifications refer to 8.5" x 11" paper of 80 g/m<sup>2</sup> weight.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
  Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.





